


MERCEDES E (213)

connector 15 pin														
OUT	OUT	OUT	OUT	OUT	OUT	OUT	OUT	OUT	OUT	OUT	OUT	OUT	OUT	OUT
—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Driver door sensor	Passenger door sensor	Trunk sense	Hood sense	Factory alarm++	Armed state	Lock factory remote	Unlock factory remote	Switches combination	Handbrake / Parking	Speed 10kmph	Engine run	Engine speed (RPM)	Ignition	Key in ignition
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+

Comments:

Switches: □ ▽ ▷ △ ▶ ⌂ ⌃ ⌄ ⌅ ⌆ ⌇ ⌈ ⌉ ⌊ ⌋ + -



ALTERNATIVE CONTROL OF CENTRAL LOCK
ALTERNATIVE TURN SIGNAL CONTROL
CAN2 connect
CAN1 connect
GND
+12V

year: 2016 → with and without Keyless System

programm Nr: XXX

from: 2014-08-25

connector 8 pin									
+	—	CAN_H	CAN_L	CAN_H	CAN_L	OUT_+/-	OUT_-/-	IN_+/-	IN_-/-
+	—	PWR +12V	SND	CAN1H	CAN1L	CAN2H	CAN2L	—	—
+	—	—	—	—	—	—	—	—	—
—	—	—	—	—	—	—	—	—	—

WIRE CONNECTING ORDER: GROUND, +12V, SET THE PROGRAM NUMBER FOR THE GIVEN VEHICLE, CONNECT CAN-L AND CAN-H.

CAN1

CAN BUS connectors
brown pin CANL
green pin CANH
CAN BUS connectors

CAN2

CAN BUS connectors
green pin CANL
green/white pin CANH
CAN BUS connectors

